

<b>Technical data MBC 601</b>		
Mains voltage	230V $\pm$ 10%; 50Hz $\pm$ 5%	
switchable to	115V $\pm$ 10%; 60Hz $\pm$ 5%	
Power draw	4 Asb (230 V); 8 Asb (115 V); 10 Asb (100 V)	
Power consumption	1000 VA	
Classification (acc. MDD)	2b	
Safety class (acc. EN 60601-1)	I	
Applied standards	EN 60 601-1; EN 60 601-2-2;	
Dimension device: W x H x D	430 x 150 x 430mm	
Weight Device	17 kg	
<b>Working data MBC 601</b>		
	Max. power output:	Max. voltage output:
Monopolar cutting	320 W / 200 $\Omega$	1320 Vpp
TUR	350 W / 200 $\Omega$	1320 Vpp
Blend (Power Blend)	250 W / 200 $\Omega$	1320 Vpp
Pulse	40 W / 200 $\Omega$	1320 Vpp
Monopolar coagulation		
Soft	100 W / 200 $\Omega$	680 Vpp
Force (Hi Force)	120 W / 200 $\Omega$	1320 Vpp
Spray	120 W / 200 $\Omega$	9000 V / 5800 V
Bipolar cutting (Bipo Pulse)	130 W / 200 $\Omega$	760 Vpp
Bipolar coagulation	100 W / 100 $\Omega$	460 Vpp